

Standard

YHK Chain No.	节距	滚子直径	内节内宽	销轴直径	销轴长度		内链板高度	链板厚度	极限拉伸载荷	平均拉伸载荷	疲劳强度
	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length		Inner plate depth	Plates thickness	Ultimate tensile strength	Average tensile strength	Fatigue
	P	d _i max	b _i min	Ld ₂ max	max	L _e max	h ₂ max	T ₁	Q _{min}	Q _o	amx
	mm	mm	mm	mm	mm	mm	mm	mm	kn	kn	kgf
415	12.7	7.75	4.88	3.96	12.5	13.9	10.4	1.3	11.6	12.5	380
420	12.7	7.77	6.35	3.96	14.5	16.1	12	1.5	16	16.5	380
428	12.7	8.51	7.75	4.45	16.5	18.05	12	1.6	17.8	18.5	380
520	15.875	10.16	6.35	5.08	17.7	19	15	2	26.5	29.5	650
525	15.875	10.16	7.94	5.08	18.8	20.5	15	2.03	26.6	29	650
530	15.875	10.16	9.4	5.08	20.9	22.2	15	2	26.5	29.7	650
630	19.05	11.91	9.4	5.94	22.2	24	18	2.4	35	37	800

Standard & Reinforced are YHK economic motorcycle chain lines. With curled bushing, Standard & Reinforced Chains are designed for low performance motorcycles with medium and low capacity up to 250CC and mopeds.

* Outer Plate Color Available: Steel
Natural Color; Black Finished;
Blue Finished; Yellow Finished

Standard

YHK Chain No.	节距	滚子直径	内节内宽	销轴直径	销轴长度		内链板高度	链板厚度	极限拉伸载荷	平均拉伸载荷	疲劳强度
	Pitch	Roller diameter	Width between inner plates	Pin diameter	Pin length		Inner plate depth	Plates thickness	Ultimate tensile strength	Average tensile strength	Fatigue
	P	d _i max	b _i min	Ld ₂ max	max	L _e max	h ₂ max	T ₁	Q _{min}	Q _o	amx
	mm	mm	mm	mm	mm	mm	mm	mm	kn	kn	kgf
415H	12.7	7.75	4.88	3.96	13.1	14.5	11.5	1.5	15.6	16.1	380
420H	12.7	7.77	6.35	3.96	15.7	17.4	12	1.8	17	17.5	380
428H	12.7	8.51	7.75	4.45	18.3	19.8	12	2.03	20.6	21.1	450
520H	15.875	10.16	6.35	5.24	18.9	20.5	15	2.42	30	31	700
525H	15.875	10.16	7.94	5.24	20.4	22.2	15	2.42	30	31	700
530H	15.875	10.16	9.4	5.08	21.9	24.2	15	2.42	30	31.5	700

可根据用户需要生产镀铜、镀锌、镀镍、镀铬链条

Copper-plated, zinc-plated, nickel-plated and chrome-plated chain available

<http://www.yhkchina.com>

E-mail: info@yhkchina.com